Model: NCM-FDB-XX

Description

NCM-FDB-XX is made of good quality composite plastic and applied widely in FTTH splitting projects. PLC splitter, box splitter and inserting plate style splitter can be installed into NCM-FDB-XX.



Fiber Distribution Box

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FDB-XX (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-FDB-XX

Item	Value				
	Split Ratio Signal Percentage %	Max Insertion Loss (dB)		Max Uniformity	P/N
		Tap	Thru		
1x8 Optical Coupler	EVEN	11		2	10274011824
1x16 Optical Coupler	EVEN	14		2	10274012640

Technical Data

Item	Unit	Value
Dimension	mm	295*335*117
Cable Diameter	mm	11.3
Cable Ports	-	16
Max Capacity of splice tray	-	up to 16 fibers
Max Capacity on main backbone cable	-	up to 24cores.
Maximum Single Fiber Count	-	24
Maximum Fiber per tray	-	16
Number of cables entry point	-	2
Color	-	white
Optimal Operating Temperature	ºC	-40 to +65

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FDB-XX (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-FDB-XX

Installation

Wall-mounting or pole-mounting (optional)



Expansion screw (wall-mounting accessories)



Stainless steel hoop (pole-mounting accessories)

NCM-FDB-XX Installation Accessories					
No.	Item	Standard	Unit	Quantity	
1	plastic wrench		pc	1	
2	bare fiber protective tube	Ø4mm	m	0.3	
3	insulating tape		pc	1	
4	figure label	1-24	set	1	
5	heat-shrinkable tube	60mm	pc	16	
6	nylon ribbon	60mm	pc	4	For heat-shrinkable tube
7	nylon ribbon	100mm	pc	4	
8	self-tapping screw	2*8mm	pc	52	For adaptor installation
9	self-tapping screw	4*25mm	pc	3	For wall mounting installation
10	plastic expansion screw	4mm	pc	3	

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FDB-XX (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com