FIBER DISTRIBUTION BOX

Model: NCM-FDB-0032

Features

- High quality cold rolled steel body, electrostatic spraying with water proof powder.
- High quality water proof lock, wall mounted cabinet.
- Operating temperature: -30°C~+55°C, storage temperature: -40°C~+60°C.
- With access to 2 pcs of 12 cores fiber optic cables and up to 32 pcs of customer cables.
- Suitable for multi-fiber optic cable access as well.
- Suitable for 36 pcs of SC, FC, ST adapters, easy to installation and maintenance.
- Support branch connection styles.



Fiber Distribution Box 1x32

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FDB-0032 (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-FDB-0032

Specifications

Item	Value				
	Split Ratio Signal Percentage %	Max Insertion Loss (dB)		Max Uniformity	P/N
		Tap	Thru		
1x32 Optical Coupler	EVEN	17.6		2.5	10274013241

Technical Data

Item	Unit	Value
Dimension	In	17x13x6
Cable Diameter	mm	10~14
Cable Ports	-	2 Holes
Max Capacity of splice tray	-	24 (Single Fiber)
Max Quantity of Splice Tray	-	2
Max Capacity on main backbone cable		12 (Single Fiber)

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FDB-0032 (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com