Model: NCM-FC- SC/APC(UPC)

Features

- Factory-installed fiber stub
- Easily installed, Quick and easy fiber termination in the field.
- Fast connecting and repeat, No special tools needed when installed.
- Can be made on-site without splicing connectors.
- Reliable optical performance
- Low insertion loss, high return loss



Fast Connector SC/APC(UPC)

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FC-SC/APC(UPC) (1.1Rev2019) © 2000-2019 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-FC- SC/APC(UPC)

Description

NCM-FC- SC/APC(UPC) are fast connectors with single mode and easy operation are compatible with 0.9mm tight buffer,2mm & 3mm drop cable.

Specifications

Item	Unit	Parameter
Insertion Loss	dB	Max<=0.5, Average<=0.3
Return Loss	dB	>=45
Durability (1000 Mating)	dB	0.2Max.
Operating Temperature	℃	-40~+75
Storage Temperature	℃	-40~+85

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-FC-SC/APC(UPC) (1.1Rev2019) © 2000-2019 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com