Ceiling-Mount Smart WIFI Access Point

Model: NCM-CWAP-22D

Features

- 1 GE WAN TX port, 2 GE LAN TX ports
- 2 Wireless modules 802.11a/b/g/n/ac, MIMO 2*2
- 5 Built-in 3dBi antenna
- Working frequency (2.412～2.4835GHz, 5.150～5.250 GHz, 5.250～5.350 GHz, 5.470～5.725 GHz, 5.745～5.825 GHz.)
- Maximum output power 24dBm/path
- WIFI AP, up to 1166Mbps wireless connectivity
- Up to 200 users' access,80 of them concurrently @2Mbps, more than 32 SSIDs



Ceiling-Mount Smart WIFI Access Point

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-CWAP-22D (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-CWAP-22D

Description

NCM-CWAP-22D ceiling-mounted intelligent WAP (3 gigabit ports, 802.11 a/b/g/n/ac, dual frequency bidirectional wireless coverage, MIMO2*2 built-in antenna, POE and Adaptor power supply)

Specifications

NCM-CWAP-22D		
Peripheral parameters	Size	180*180*25mm
	Weight	≤300g
	Power Supply	802.3at POE (suggested)
	Power consumption	Peak value ≤ 20W
	Working temperature	-10℃ to 50℃
	Working humidity	5%-95% (non-condensing)

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-CWAP-22D (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

Model: NCM-CWAP-22D

Software Specifications

Item	NCM-CWAP-22D	
Working mode	FAT AP	Support
	FiT AP	
Protocols	802.1Q VLAN, 4K	Support
	802.1p priority queue	
	IPv6 Passthrough	
	DHCP snooping	
	IGMP proxy	
	DHCP Server	
	NAT	
	PPPoE	
	SNMP	
	SNTP	
Wireless security	WPA-Personal/Enterprise	Support
	WPA2-Personal/Enterprise	
	WEP 64/128-bit Encryption	
	EAP-SIM/EAP-AKA/EAP-MD5/EAP-TLS/EAP-TTLS/PEAP	
	SSID broadcast disable	
	MAC address filtering	
	802.1x RADIUS client with PAP/CHAP	
WLAN attributes	User isolation	Support
	Fair receiving time	
	Automatic channel choice	
	Automatic power control	
	Wireless terminal identification	
	5G access	
Management mode	Web	Support
	Telnet	
	CLI	
	AC centralized management	
	SNMP	

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-CWAP-22D (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com