OPTICAL COUPLER RACK MOUNT

Model: NCM-OC-RM

Features

- FTTx and HFC Applications
- Rack Mount 19”
- Low Insertion Loss
- High variety of Split Ratios available
- 1310-1550 Double Window Optical Spectrum
- Single Mode Fiber
- High Quality Optical Connectors



1RU Rack Mount 19” PLC Splitter

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-OC-RM (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com

OPTICAL COUPLER RACK MOUNT

Model: NCM-OC-RM

Specifications

Item	Value				
	Split Ratio Signal Percentage %	Max Insertion Loss (dB)		Max Uniformity	P/N
		Tap	Thru		
1x4 Optical Coupler	25/25/25/25	7.5/7.5/7.5/7.5		1.5	10206011419
	10/10/20/60	11.5/11.5/8.5/3.7			10206011420
	10/20/30/40	11.5/8.5/6.7/55			10206011421
	20/20/30/30	8.5/8.5/6.7/6.7			10206011422
1x8 Optical Coupler	EVEN	11		2	10206011824
1x16 Optical Coupler	EVEN	14		2	10206012640

Technical Data

Parameter	Unit	Value
Return Loss	dB	≥ 55
Uniformity of I. L	dB	≤1.5
PDL	dB	≤0.20
Directivity	dB	≥ 55
Operating Temperature/Humidity	°C	-40 to +85 / 90%
Storage Temperature/Humidity	°C	-40 to +85 / 90%
Maximum Input Power	mW	500
Dimensions	mm	465X265X85

Unless otherwise noted, the above specifications reflect typical device performance at stated reference levels in the recommended operating configuration(s). Specifications are subject to change without notice.

NCM-OC-RM (1.1Rev2018) © 2000-2018 NCM Supplies – All Rights Reserved

NCM Supplies Inc.
8125 NW 64th ST. Miami, Florida 33166
Phone: 305-640-0461 Fax: 305-639-2684
ncm@ncmsupplies.com | www.ncmsupplies.com